

Newfoundland Labrador Hydro (NLH) Supply and Demand Status Report Filed Friday, July 21, 2017

Supply Notes For July 20, 2017

- A As of 2003 hours, May 03, 2017, Bay d'Espoir Unit 3 unavailable due to planned outage (76. 5 MW).
- **B** As of 1858 hours, June 22, 2017, Stephenville Gas Turbine available at 25 MW (50 MW).
- **C** As of 0938 hours, June 23, 2017, Holyrood Unit 1 unavailable due to planned outage 120 MW (170 MW).
- **D** As of 1851 hours, July 02, 2017, Holyrood Unit 2 available at 165 MW (170 MW).

1,2

- E As of 0604 hours, July 03, 2017, Bay d'Espoir Unit 2 unavailable due to planned outage (76. 5 MW).
- **F** As of 1018 hours, July 07, 2017, Granite Canal Unit unavailable due to planned outage (40 MW).
- G As of 1314 hours, July 11, 2017, St. Anthony Diesel Plant available at 8.85 MW (9.7 MW).
- **H** As of 2000 hours, July 14, 2017, Holyrood Unit 3 available but offline for economic dispatch (150 MW).
- As of 0653 hours, July 19, 2017, Cat Arm Unit 2 unavailable due to planned outage (67 MW).
- J At 0814 hours, July 20, 2017, Bay d'Espoir Unit 1 unavailable due to planned outage (76. 5 MW).
- K At 1611 hours, July 20, 2017, Bay d'Espoir Unit 1 available (76. 5 MW).

Fri, Jul 21, 2017 Island	lsi System Outlook ³		Seven-Day Forecast	Tempe (°	rature C)	Island System Daily Peak Demand (MW
	,			Morning	Evening	Forecast
Available Island System Supply: ⁵	1,380	MW	Friday, July 21, 2017	14	17	780
NLH Generation: ⁴	1,080	MW	Saturday, July 22, 2017	18	17	755
NLH Power Purchases: ⁶	100	MW	Sunday, July 23, 2017	14	14	765
Other Island Generation:	200	MW	Monday, July 24, 2017	15	16	785
Current St. John's Temperature:	13	°C	Tuesday, July 25, 2017	14	13	770
Current St. John's Windchill:	N/A	°C	Wednesday, July 26, 2017	13	12	800
7-Day Island Peak Demand Forecast:	825	MW	Thursday, July 27, 2017	10	12	825
supply. The power system op supply reserves are available. 2. Due to the Island Interconnec must be interrupted for short frequency load shedding, is n	erators schedule out However, from time ted System being ise periods to bring gen ecessary to ensure t	utages to ne to time solated fr eneration the integ	nce are included. These are not unusual for p system equipment whenever possible to co e equipment outages are necessary and rese rom the larger North American grid, when th output equal to customer demand. This aut grity and reliability of system equipment. Un r load interruptions are generally less than 30	incide with periods w rves may be impacted nere is a sudden loss o comatic action of pow der frequency events	nen customer I. f large genera er system pro	demands are low and sufficient ating units some customer's load otection, referred to as under
 supply. The power system op supply reserves are available. 2. Due to the Island Interconnect must be interrupted for short frequency load shedding, is n Island Interconnected System 3. As of 0800 Hours. 4. Gross output including station 5. Gross output from all Island s 	erators schedule out However, from time ted System being ise periods to bring gen ecessary to ensure to and the resultant co n service at Holyrood ources (including No	utages to ne to time solated fr eneration the integ customer od (24.5 N ote 4).	system equipment whenever possible to co e equipment outages are necessary and rese rom the larger North American grid, when th output equal to customer demand. This aut grity and reliability of system equipment. Un	incide with periods we erves may be impacted ere is a sudden loss o comatic action of powe der frequency events D minutes. e to water levels (35 M	nen customer I. f large genera er system pro typically occu 1W).	r demands are low and sufficient ating units some customer's load otection, referred to as under ur 5 to 8 times per year on the
 supply. The power system op supply reserves are available. 2. Due to the Island Interconnect must be interrupted for short frequency load shedding, is n Island Interconnected System 3. As of 0800 Hours. 4. Gross output including station 5. Gross output from all Island s 	erators schedule out However, from time ted System being iso periods to bring gen ecessary to ensure t and the resultant con n service at Holyrood ources (including No CBPP Co-Gen, Nalc	utages to ne to time solated fr eneration the integ customer od (24.5 N ote 4). lcor Explo	system equipment whenever possible to co e equipment outages are necessary and rese rom the larger North American grid, when the noutput equal to customer demand. This aut grity and reliability of system equipment. Un load interruptions are generally less than 30 MW) and improved NLH hydraulic output due bits, Rattle Brook, Star Lake, Vale capacity as Section 3 Island Peak Demand Informa	incide with periods we erves may be impacted ere is a sudden loss of comatic action of powe der frequency events 0 minutes. e to water levels (35 M sistance (when applice tion	hen customer I. f large genera er system pro typically occu 1W). able), and Wi	r demands are low and sufficient ating units some customer's load otection, referred to as under ur 5 to 8 times per year on the
 supply. The power system op supply reserves are available. 2. Due to the Island Interconnect must be interrupted for short frequency load shedding, is n Island Interconnected System 3. As of 0800 Hours. 4. Gross output including station 5. Gross output from all Island s 6. NLH Power Purchases include 	erators schedule out However, from time ted System being iso periods to bring gen ecessary to ensure t and the resultant con n service at Holyrood ources (including No CBPP Co-Gen, Nalc	evious	system equipment whenever possible to co e equipment outages are necessary and rese rom the larger North American grid, when the noutput equal to customer demand. This aut grity and reliability of system equipment. Un cload interruptions are generally less than 30 MW) and improved NLH hydraulic output due bits, Rattle Brook, Star Lake, Vale capacity as Section 3	incide with periods we erves may be impacted ere is a sudden loss of comatic action of powe der frequency events 0 minutes. e to water levels (35 M sistance (when applice tion	hen customer I. f large genera er system pro typically occu 1W). able), and Wi	r demands are low and sufficient ating units some customer's load otection, referred to as under ur 5 to 8 times per year on the