

Newfoundland Labrador Hydro (NLH)

otes:	1.	 Generation outages for running and corrective maintenance are included. These are not unusual system operators schedule outages to system equipment whenever possible to coincide with per from time to time equipment outages are necessary and reserves may be impacted. 		•	•		
	 Due to the Island system having no synchronous connections to the larger North American grid, when there is a sudden loss of large generating units there may be a requirement for some customer's load to be interrupted for short periods to bring generation output equal to customer demand. This automatic action of power system protection, referred to as under frequency load shedding (UFLS), is necessary to ensure the integrity and reliability of system equipment. Under frequency events have typically occurred 5 to 8 times per year on the Island Interconnected System and the resultant customer load interruptions are generally less than 30 minutes. With the activation of the Maritime Link frequency controller during the winter of 2018, UFLS events have occurred less frequently. 						
	3.						
	4.	4. Gross output including station service at Holyrood (24.5 MW) and improved NLH hydraulic outp	ut due to water levels (35 MW).				
	5.						
	6.	6. NLH Island Power Purchases include: CBPP Co-Gen, Nalcor Exploits, Rattle Brook, Star Lake, Win	d Generation and capacity assistance (wh	en applicable)			
	7	7. Adjusted for curtailable load, market activities and the impact of voltage reduction when application	able				

	Section 3 Island Peak Demand Information	on							
Previous Day Actual Peak and Current Day Forecast Peak									
Wed, Sep 11, 2019	Actual Island Peak Demand ⁸	19:50	788 MW						
Thu, Sep 12, 2019	Forecast Island Peak Demand		840 MW						