
### Newfoundland Labrador Hydro (NLH) Supply and Demand Status Report Filed Monday, February 07, 2022

## Section 1 Island Interconnected System Supply, Demand & Exports Actual 24 Hour System Performance For Sunday, February 06, 2022



Supply Notes For February 06, 2022

12

As of 1715 hours, January 21, 2022, Holyrood Unit 2 available at 150 MW (170 MW).

#### Section 2

**Island Interconnected Supply and Demand Temperature Island System Daily** Island System Outlook<sup>3</sup> Peak Demand (MW) Mon, Feb 07, 2022 (°C) Seven-Day Forecast Adjusted<sup>\*</sup> Morning **Evening Forecast** Available Island System Supply:5 1,875 1,765 -7 2,320 MW Monday, February 07, 2022 -12 NLH Island Generation:<sup>4,8</sup> 1,415 1,311 1,675 -3 -2 MW Tuesday, February 08, 2022 1,212 NLH Island Power Purchases:6 Wednesday, February 09, 2022 5 0 1,315 105 MW Other Island Generation: 225  $\mathsf{M}\mathsf{W}$ Thursday, February 10, 2022 -1 -1 1,290 1,187 MW Friday, February 11, 2022 2 1 1,215 1,113 ML/LIL Imports: 315 °C Current St. John's Temperature & Windchill: -14 °C Saturday, February 12, 2022 -21 -4 1 1,260 1,157 Sunday, February 13, 2022 7-Day Island Peak Demand Forecast: 3 1,875 MW 1,320 1,217

#### Supply Notes For February 07, 2022

Notes:

- 1. Generation outages for running and corrective maintenance are included. These are not unusual for power system operations. They generally do not impact customer supply. The power system operators schedule outages to system equipment whenever possible to coincide with periods when customer demands are low and sufficient supply reserves are available. However, from time to time equipment outages are necessary and reserves may be impacted.
- 2. Due to the Island system having no synchronous connections to the larger North American grid, when there is a sudden loss of large generating units there may be a requirement for some customer's load to be interrupted for short periods to bring generation output equal to customer demand. This automatic action of power system protection, referred to as under frequency load shedding (UFLS), is necessary to ensure the integrity and reliability of system equipment. Under frequency events have typically occurred 5 to 8 times per year on the Island Interconnected System and the resultant customer load interruptions are generally less than 30 minutes. With the activation of the Maritime Link frequency controller during the winter of 2018, UFLS events have occurred less frequently.
- 3. As of 0800 Hours.
- 4. Gross output including station service at Holyrood (24.5 MW) and improved NLH hydraulic output due to water levels (35 MW).
- 5. Gross output from all Island sources (including Note 4).
- 6. NLH Island Power Purchases include: CBPP Co-Gen, Nalcor Exploits, Rattle Brook, Star Lake, Wind Generation and capacity assistance (when applicable).
- 7. Adjusted for curtailable load, market activities and the impact of voltage reduction when applicable.
- 8. Due to limitations inherent in the design of combustion turbines, the output of combustion turbines may be reduced in the event that ambient temperatures exceed the threshold required for full rated output. This threshold is dependent on the design of each turbine.

# Section 3 Island Peak Demand Information Previous Day Actual Peak and Current Day Forecast Peak Sun, Feb 06, 2022 Actual Island Peak Demand 9 17:50 1,767 MW Mon, Feb 07, 2022 Forecast Island Peak Demand 1,875 MW

Notes: 9. Island Demand / LIL / ML Exports (where applicable) is supplied by NLH generation and purchases, plus generation owned and operated by Newfoundland Power and Corner Brook Pulp & Paper (Deer Lake Power, DLP).